



## CLEAR LOOK PAVERS PROTECTOR (EV)



### UPDATE

**February 4, 2011**

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: [techniseal.com](http://techniseal.com)

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

- Recommended for driveways parking lots, patios and walkways

### PROPERTIES

- Preserves the natural color of pavers
- Optimal oil repellency
- Single coat application
- Water-based

### DESCRIPTION

Made of acrylic and urethane, TECHNISEAL® CLEAR-LOOK PAVER PROTECTOR (EV) is a semi-gloss, microporous transparent coating that protects pavers made of concrete. It reduces oil and dirt penetration, and makes cleaning easier. Easy to apply, it penetrates the surface for maximum adhesion and durability. CLEAR-LOOK PAVER PROTECTOR will not peel or discolor. It resists the elements (freeze-thaw cycles, sun, rain, etc.), as well as calcium and salt. It also resists hot tire pick-up. Water-based, CLEAR-LOOK PAVER PROTECTOR does not give off unpleasant fumes and is environmentally friendly.

### DIRECTIONS

Wear adequate protective clothing.

**ALWAYS TEST** the product on a small hidden area of approximately 4 sq. ft. to ensure the results will meet your expectations.

Do not thin or dilute. Keep from freezing.

Apply only to bare material or to material that has been previously sealed with a compatible TECHNISEAL® PROTECTOR. Wait until the surface of the previous PROTECTOR is completely worn off before recoating (minimum of 2 years).

**New concrete pavers:** Efflorescence (whitish salt) may appear on such materials within 60 days following installation. Wait at least 60 days before cleaning and sealing. Applying a PROTECTOR before 60 days may cause blotchiness of the surface.

**Newly installed polymeric sand on older pavers:** Wait at least 30 days before cleaning and sealing pavers.

**Slipperiness:** This product can make the surface more slippery when wet. The application of matte-finish NATURAL-LOOK (iN) PROTECTOR is recommended where slipperiness represents a cause for concern. Results will vary according to paver type and porosity. Proper surface priming is essential.

## PREPARATION

**Stain removal:** If necessary, remove any stains (oil, rust, etc.) from the surface using the appropriate TECHNISEAL® stain remover.

**Priming:** This step is essential to obtain an optimal and uniform semi-gloss finish. Prime the entire surface by removing all efflorescence and ground-in dirt. This ensures a uniform look and allows the PROTECTOR to better penetrate the surface. Use TECHNISEAL® PAVER PRIMER/EFFLORESCENCE CLEANER for pavers with efflorescence or pavers less than 5 years old. Use Techniseal® HC HARDSCAPE CLEANER for surfaces without efflorescence or pavers more than 5 years old.

Proper rinsing is essential.

## APPLICATION:

Surface must be clean, dry (24 hours without precipitation) and warm to the touch (morning). Joints must also be dry. Temperature must be between 50°F and 80°F, and rain should not be forecasted over the following 24 hours. Sprinklers must be shut off. For optimal results, apply product under constant weather conditions and using the same application method from start to finish. Shake container or stir product before use.

The level of saturation obtained will determine the intensity of the semi-gloss finish.

**Roller application:** Using a regular foam roller (non-slit) and a paint tray, saturate the surface with a single coat of PROTECTOR.

**Sprayer application:** Soak the surface using an airless or pump sprayer.

Once a section of approximately 150 sq. ft. has been rolled or sprayed, back-roll any excess PROTECTOR with a foam roller, before it dries.

**Note:** If product is not applied uniformly or sufficiently, some blotchiness could be visible when surface is wet but will return to normal when dry.

Let dry for 24 hours before walking on the surface and 48 hours before allowing traffic.

**Cleaning of tools:** Use water and soap.

## COVERAGE

1 gal. covers up to 150 sq. ft. Coverage will depend on surface porosity and joint width.

Cleaning yearly with TECHNISEAL® HC HARDSCAPE CLEANER will keep pavers looking fresh.

## STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. Properly stored, the product's shelf life is 3 years following production (see date on packaging).

## PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
121-303	1 gal.	4	180
121-306	5 gal.	—	48
221-308	55 gal.	—	4

## WARNING

---

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **FIRST AID:** In case of contact, immediately flush eyes and skin with plenty of water. If irritation persists, get medical attention. **CONTAINS:** Acrylic Polymers. **KEEP OUT OF REACH OF CHILDREN.** Calculated VOC: >100 g/L

## SHIPPING

---

### Land and sea

NOT REGULATED

## LIMITED WARRANTY

---

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m<sup>2</sup>). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.