



RG+ Concrete Adhesive for Walls, Pavers and Slabs



UPDATE

March 15, 2010

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Retaining walls, pavers and slabs
- Any concrete or masonry surface

DESCRIPTION

- Specially formulated for the construction of concrete hardscapes, TECHNISEAL RG+ CONCRETE ADHESIVE FOR WALLS, PAVERS AND SLABS is a first-quality product designed to resist the elements (water, frost, etc.). It provides a strong and durable bond.

DISTINCTIVE FEATURES

Elastomeric-resin-based compound. Remaining flexible, it is ideal for the construction of retaining walls. Most effective on dry surfaces. Can also be used on wet or frozen surfaces (allow for longer curing period).

DIRECTIONS

Wear adequate protective clothing. **To ensure the results will meet your expectations, it is advisable to test the product on a small hidden area.**

Surface should be clean and, ideally, dry. Apply a maximum thickness of 3/8"; join pieces together immediately with a slight twisting motion.

COVERAGE

1 quart makes a bead 0.4" in diameter by 32 to 36 linear feet.

STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 2 years following production (see date on packaging).

PACKAGING

Name	Product Code	Retail Size	Units per box	Units per pallet
RG+	221-791	10 fl. oz.	12	1,296
	221-792	28 fl. oz.	12	456

WARNING

DANGER. EXTREMELY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE FLASH FIRE. MAY CAUSE SKIN AND EYE IRRITATION. MAY BE HARMFUL IF LARGE AMOUNTS ARE INHALED. **CONTAINS:** Acetone, hexane and toluene. **Warning:** This product contains toluene which is known to the State of California to cause birth defects or other reproductive harm. Use only with adequate (positive cross) ventilation. Avoid contact with skin, eyes and clothing. Avoid breathing vapors. Do not take internally. Prolonged or repeated overexposure to solvents in uncured product can cause nervous system, liver, kidney and respiratory effects. Keep away from heat, sparks and flames. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** If dizziness or other adverse effects occur, remove to fresh air. If ill effects continue, call a physician or Poison Control Center. In case of contact: for eyes, flush with water for 15 minutes; for skin, wash thoroughly with soap and water. If irritation persists, contact a physician. Wear rubber gloves when handling. Use entire contents on opening. Calculated VOC (less exempt solvent): 282 g/L.

FOR PROFESSIONAL USE ONLY

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET

SHIPPING

Land and Sea

HP PRO:

NOT REGULATED

RG:

ADHESIVES containing flammable liquid

Class: 3

UN Number: 1133

Packing Group: III

(Limited Quantity)

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal can not guarantee the results. Techniseal warranty is limited to the replacement of product proven defective. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.