



UPDATE

February 22, 2010

U.S.A. and Canada: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

Product and company identification:

Product name: Rust Remover for pavers and slabs

Material uses: Takes out rust from pavers and slabs made of concrete

Supplier/Manufacturer: Techniseal

300, avenue Liberté

Candiac, QC, Canada, J5R 6X1

Tel: (514) 523-2110 Toll free: 1-800-465-7325 Fax: (450) 633-3035

In case of emergency: CANUTEC (613) 996-6666

First aid measures:

Eye contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention immediately.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. **Notes to physician:** No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Fire-fighting measures:

Flammability of the product: Not flammable

Extinguishing media:

Suitable: Use water spray, dry chemical powder or carbon dioxide for extinction.

Not suitable: None known

Hazardous thermal decomposition products: Decomposition products may include the following materials: phosphorus oxides.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Disposal considerations:

Waste disposal: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers..

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Other information:

Label requirements

: CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY BE HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



HAZARD RATINGS

4- Extreme 3- Serious

2- Moderate 1- Slight

0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



References

: ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005.